

SOFAR 15K~24KTLX-G3

15 / 17 / 20 / 22 / 24 kW

THREE-PHASE DUAL MPPT



Product advantages

- Maximum efficiency 98.6%
- Low start-up voltage, wide MPPT voltage
- Maximum DC input voltage 1100 V
- Smart string level monitoring
- Type II SPD for both DC and AC side
- Remote firmware upgrade
- 110% long-time overload ability



Datasheet	SOFAR 15KTLX-G3	SOFAR 17KTLX-G3	SOFAR 20KTLX-G3	SOFAR 22KTLX-G3	SOFAR 24KTLX-G3
Input (DC)					
Max. input voltage	1100V				
Rated input voltage	650V				
Start-up voltage	160V				
MPPT operating voltage range	140V-1000V				
Number of MPP trackers	2				
Number of DC inputs	2/2				
Max. input MPPT current	26A/26A	26A/26A	26A/26A	26A/26A	26A/26A
Max. input short circuit current	36A/36A	36A/36A	36A/36A	36A/36A	36A/36A
Output (AC)					
Rated output power	15000W	17000W	20000W	22000W	24000W
Max. apparent power	16500VA	18700VA	22000VA	24200VA	26400VA
Max. output current	23.9A	27.1A	31.9A	35.1A	38.3A
Rated output voltage	3/N/PE, 230V/400Vac				
Output voltage range	310Vac-480Vac				
Rated output frequency	50/60Hz				
Output frequency range	45Hz-55Hz/55Hz-65Hz				
Active power adjustable range	0-100%				
THDI	<3%				
Power factor	1 (adjustable +/-0.8)				
Efficiency					
Max. efficiency	98.6%	98.6%	98.6%	98.6%	98.6%
European efficiency	98.2%	98.2%	98.2%	98.2%	98.2%
Protection					
DC reverse polarity protection	Yes				
Anti-islanding protection	Yes				
Leakage current protection	Yes				
Ground fault monitoring	Yes				
PV-array string fault monitoring	Yes				
DC switch	Yes				
SPD	PV: type II, AC: type II				
General Data					
Ambient temperature range	-30 C--+60 C				
Self-consumption at night	<1W				
Topology	Transformerless				
Degree of protection	IP65				
Allowable relative humidity range	0-100%				
Max. operating altitude	4000m				
Cooling	Smart air cooling				
Dimension (W×H×D)	520×430×189mm				
Weight	20kg	22kg	22kg	23kg	23kg
Display	LCD & Bluetooth +APP				
Communication	RS485/WIFI				
Standard	IEC/EN 61000-6-1/3, IEC/EN 61000-3-11/12, IEC 62116, IEC 61727, IEC 61683, IEC 60068-1/2/14/30, IEC/EN 62109-1/2 G99, VDE-AR-N 4105, VDE V 0126-1-1, CEI0-21, EN 50549-1, NRS 097-2-1				

*All specifications are subject to change without notice.

03 / 2023—V2