#### **Energy Storage**



### **Features**



### **PERFORMANCE**

- Ultra capacity up to 16.076kWh
- Parallel Connection up to 4 units / 64.288kWh
- Superstandard 314Ah battery cell performance up to 1C
- Standing battery pack achieves 8000 Cycle Life with EOL 70% @0.5C



# **SMART MANAGE**

- · Realtime monitoring via App & Web
- · RS485/CAN to inverters
- Passive Balancing
- · Over-the-air upgrade



# **APPLICABILITY**

- Perfectly adapted to wide range of operating environment.
- Lock castors ensures easy moving while installation



# **RELIABILITY**



- Natural Cooling with higher efficiency and longer life span.
- Cmmprehensive electrical protection design avoiding danger from lightening, over voltage/current, leakage, electrostatic interference, etc.



## **SAFETY**

- High reliable lithium battery cell adopted.
- Advanced Battery Management System monitoring and protection for each battery cell.
- DC Breaker



**Energy Storage** 

COMPANY	SKYWORTH ENERGY STORAGE
ADD	A606, Skyworth Building
	Gaoxin 1s Rd, Nanshan, Shenzhen
	518053 CHINA
WEB	www.skyworthes.com

### LV MAX PRODUCT DATASHEET

BatteryType	LiFePO <sub>4</sub>
Rated Capacity	16.076kWh
Usable Capacity	15.27kWh (D0D 95%, 0.5C)
Rated Voltage	51.2V
Operating Voltage Range	40~58.4V
Rated Charging Current	150A
Rated Discharging Current	150A
Max. Chargering/Dicharging Current	170A
Balancing Method	Passive Balancing
Cycle Life	≥8000 cycles @ 25° <b>C</b> with 0.5C 70%EOL
Communication	WiFi Dongle,RS485/CAN
Operating Temperature	Charging: 0°C~55°C / Discharging: -20°C~60°C
Storage Temperature	-20°C~45°C
Operating Humidity	5~95%
Operating Altitude	≤3000m
Cooling Method	Natural Cooling
Ingress Protection	IP20 for indoor installation.
Parallel Connection	 ≤4
Indicator	Color Bar (showing SOC and battery status)
Remote Management	Over-the-air upgrade, Realtime management via App & Web
General Information	
Weight	Approx.125kg
Dimension (WxDxH)	610 x270x833mm (With wheels)
	Loading capacity: 90 PCS per 20' GP container
Mounting Method	Floor-Stand (with lock castors)
Certification	UN38.3, MSDS, IEC62619, EMC, etc.
Warranty	10 years